






















GENUINE MACKENZIE VALLEY FURS (GMVF) NECK SNARE GUIDE 2005-2007

GMVF Programs comply with the Agreement on International Humane Trap Standards (AIHTS).

All snares on this chart are acceptable for use under GMVF Programs.

	Bottom of loop to ground	Loop Size	Cable Description	Cable length	Lock Size	Snare
Beaver 	lower snare must be 11cm (4½ in.) from bottom	20-25cm (8-10 in)	¾ in. or ⅛ in. airplane cable	39 in. plus double 18-gauge tail wire	Small 	
Lynx 	30cm (12 in.)	20cm (8 in.)	⅛ in. or ¾ in. airplane cable with sliding lock	42in.	Small 	
Fox 	18cm (7 in.)	18cm (7 in.)	⅛ in. or ¾ in. airplane cable with sliding lock	4 ft.	Small 	
Coyote 	25cm (10 in.)	25cm (10 in.)	⅝ in. and ⅜ in. airplane cable with sliding lock or 1x19 power snare	6 ft.	Medium or Small 	
Wolf 	35cm (14 in.)	35cm (14 in.)	⅜ in. and ⅛ in. airplane cable with sliding lock or 1x19 power snare	10 ft. - 12 ft.	Large 	
Wolverine 	18cm (7 in.)	25cm (10 in.)	⅜ in. and ⅛ in. airplane cable with sliding lock or 1x19 power snare	2 ft. plus #9 wire as required	Medium or Large 	
Squirrel 	1in. to 1-¼ in. from pole	1-¾ in.	24 gauge brass or 16 pound test Wms Monel steel wire	20 in.	Lock not required	